


# PRICE LIST 2023



## DODIA ELECTRICALS



### AUTOMATION BRAND



### SWITCHGEAR BRAND





EAPL

# Maximum Retail Price

Year 2023-2024

(Valid upto 31st March 2024)

HSN Code	Model	Product Description	Voltage	Time Range	Unit price (Rs.)
<b>A Series</b>					
<b>General Description Rly 2c/o,</b>					
9106 90 00	A1D1	ON Delay timer	240V AC	0.3S-30M	1010
9106 90 00	A1D1-X	ON Delay timer	X' Vtg	0.3S-30M	1070
9106 90 00	A1D1-X(60M)	ON Delay timer Rly 2C/O	X' Vtg	0.6S-60M	1070
9106 90 00	A1DCS-X	Cyclic Equal OFF-ON timer Rly2C/O	X' Vtg	0.6S-60M	1160
9106 90 00	A1DE-X	Interval timer 'X'Vtg Rly2C/O	X' Vtg	0.3S-30M	1130
<b>General Description ON Delay timer, Rly 2 c/o, CE</b>					
9106 90 00	A1D1	ON Delay timer, Rly 2 c/o, CE	240V AC	0.3S-30M	1150
9106 90 00	A1D1-X	ON Delay timer, Rly 2 c/o, CE	X' Vtg	0.3S-30M	1160
9106 90 00	A1D1-X(60M)	ON Delay timer, Rly 2 c/o, CE	X' Vtg	0.6S-60M	1190
<b>General Description ON Delay timer, Rly 2c/o, UL</b>					
9106 90 00	A1D1	ON Delay timer, Rly 2c/o, UL	240V AC	0.3S-30M	1230
9106 90 00	A1D1-X	ON Delay timer, Rly 2c/o, UL	X' Vtg	0.3S-30M	1240
9106 90 00	A1D1-X(60M)	ON Delay timer, Rly 2c/o, UL	X' Vtg	0.6S-60M	1240
9106 90 00	A1DE-X	Interval timer, Rly 2c/o, UL	X' Vtg	0.3S-30M	1250
9106 90 00	A1DCS-X	Cyclic Equal OFF-ON timer,Rly 2c/o, UL	X' Vtg	0.6S-60M	1250
9106 90 00	A1DN-X	Auxiliary Relay, Rly 2c/o, UL	X' Vtg	20mS	830
<b>General Description ON Delay Timer</b>					
9106 90 00	A1D1	8V-30V DC, Rly 2C/O	8V-30V DC	0.3S-30M	1160
9106 90 00	A1D1(WB)	Wide band V2.0, Rly 1C/O	264V-456VAC	3S-30S	1110
<b>General Description Signal OFF delay Timer, Rly 1C/O, Signal - free from external voltage</b>					
9106 90 00	A1DA	Signal OFF Delay timer, 240V AC	240V AC	0.3S-30M	1190
9106 90 00	A1DA	Signal OFF Delay timer, 110V AC	110V AC	0.3S-30M	1190
<b>General Description Star Delta Timer, Rly 1C-NO - Star, 1C-NO-Delta,TD 40mS/100mS</b>					
9106 90 00	A1DS	Star Delta Timer 240V AC	240V AC	0.6S-60S	980
9106 90 00	A1DS	Star Delta Timer 110V AC	110V AC	0.6S-60S	980
9106 90 00	A1DS	Star Delta Timer 415V AC	415V AC	0.6S-60S	980
<b>General Description Anti pumping Relay, 'X' Vtg, 80mS</b>					
8536 90 00	APD-100	Rly 1C/O, 80mS	X'Vtg	80mS	680
8536 90 00	APD-300	Rly 2C/O, 80mS	X'Vtg	80mS	780
8536 90 00	APD-500	Auxiliary Relay,20mS Rly 4C/O	X'Vtg	20mS	1030
<b>General Description Misc, Rly 2c/o</b>					
9106 90 00	A1DN-X	Auxiliary Relay	X' Vtg	20mS	800
9106 90 00	A1DH-1	Power OFF Delay timer,	240VAC	18S-180S	1150
9106 90 00	A1DCA-X	Cyclic ON-OFF Adjustable timer	X'Vtg	6S-60M	1220
9106 90 00	A1DM-X	Multifunction timer	X'Vtg	0.1M-10H	1250
<b>B Series</b>					
<b>General Description Cyclic ON-OFF Adjustable timer, Rly2C/O</b>					
9106 90 00	B1DCA-X	0.6sec to 60M	X'Vtg	0.6S-60M	1410
9106 90 00	B1DCA-T	0.1S-10H	110VAC	0.1S-10H	1410
9106 90 00	B1DCA-T	0,1S-10H	240VAC	0.1S-10H	1410
<b>General Description ON Delay Timer with instant contact, Rly 1C/O instt, 1C/O ONDly</b>					
9106 90 00	B1DF	240V AC	240V AC	0.3S-30M	1410
9106 90 00	B1DF	110V AC	110V AC	0.3S-30M	1410

X' Voltage: 24 VAC to 240 V AC, 24 V DC to 220 V DC

HSN Code	Model	Product Description	Voltage	Time Range	Unit price (Rs.)
<b>General Description Misc</b>					
9106 90 00	B1DS	Star Delta timer, TD 40mS/100mS, Rly1C-NO-Star, 1C-NO-Delta	440V AC	0.6S-60S	1570
9106 90 00	B1DH-Q	Power OFF Delay timer Rly2C/O	110-240V AC / 110-220V DC	6S-60S	1760
<b>ETR Series</b>					
<b>General Description 'X' Vtg, Rly1C/O</b>					
9106 90 00	ETR1-X	ON Delay timer Multirange	'X'Vtg	0.3S-30M	670
9106 90 00	ETRCs-X	Cyclic Equal OFF-ON timer Multirange	'X'Vtg.	0.6S-60M	670
9106 90 00	ETRE-X	Interval timer Multirange	'X'Vtg	0.3S-30M	670
9106 90 00	ETRN-X	Auxiliary Relay	'X'Vtg	20mS	630
<b>General Description Star Delta timer, 240V AC, TD-100mS, Rly 1C-NO-star, 1C-NO-Delta</b>					
9106 90 00	ETR-S	6S-60S	240 VAC	6S-60S	670
9106 90 00	ETR-Sa	12S-120S	240 VAC	12S-120S	670
<b>S Series</b>					
<b>General description Sequential timer, 1Rly (1C-NO) per chnl</b>					
9106 90 00	ST-4M1	4Channel timer	240 V AC	0.1S-1H	2720
9106 90 00	ST-6M1	6Channel timer	85-270V AC/DC	0.1S-99H 59M	7020
9106 90 00	ST-10M1	10Channel timer	85-270V AC/DC	0.1S-99H 59M	8610
9106 90 00	ST-6M1(IP)	6Channel timer, IP66	85-270V AC/DC	0.1S-99H 59M	8380
9106 90 00	ST-10M1(IP)	10Channel timer, IP66	85-270V AC/DC	0.1S-99H 59M	10270
<b>General description Sequential timer, 1Triac per chnl</b>					
9106 90 00	ST-10M2	10Channel timer	85-270V AC/DC	0.01S-99H 59M	9010
9106 90 00	ST-10M2(IP)	10Channel timer, IP66	85-270V AC/DC	0.01S-99H 59M	10280
9106 90 00	ST-15M2	15Channel timer	85-270V AC/DC	0.01S-99H 59M	7120
9106 90 00	ST-15M2(IP)	15Channel timer, IP66	85-270V AC/DC	0.01S-99H 59M	8640
<b>General description Combination timer, 1Rly (1C-NO) per chnl</b>					
9106 90 00	S1DC8-M3	8 Channel timer	85-270V AC/DC	1S-99H59M	11480
<b>H Series</b>					
<b>General description ON Delay timer (11pin, plug-in-type), 'X' Vtg, Rly 2C/O</b>					
9106 90 00	H1DT-10	10S	'X' Voltage	1S-10S	1120
9106 90 00	H1DT-30	30S	'X' Voltage	3S-30S	1120
9106 90 00	H1DT-60	60S	'X' Voltage	6S-60S	1120
<b>General description ON Delay timer (8pin, plug-in-type), 'X' Vtg, Rly 2C/O</b>					
9106 90 00	H4DT-10	10S	'X' Voltage	1S-10S	1120
9106 90 00	H4DT-30	30S	'X' Voltage	3S-30S	1120
9106 90 00	H4DT-60	60S	'X' Voltage	6S-60S	1120
<b>General description Multi function Timer, 'X' Vtg, Rly 2C/O</b>					
9106 90 00	H3D1	8 terminals	'X' Voltage	0.3S-60M	1120
9106 90 00	H1D1-X	11pin, plug-in-type	'X' Voltage	0.3S-60M	1200
<b>General description Others</b>					
9106 90 00	H1DA-X	Signal OFF Delay timer (11pin, plug-in-type), Rly2C/O	'X' Voltage	0.6S-60M	1200

'X' Voltage: 24 VAC to 240 V AC, 24 V DC to 220 V DC

HSN Code	Model	Product Description	Aux.Voltage	Stdby Voltage	Unit Price (Rs.)
<b>Annunciators - M2 Series</b>					
8531 20 00	M2-4	4 Windows	85-270V AC/DC 18-90 V AC/DC	-	2670
8531 20 00	M2-6	6 Windows	85-270V AC/DC 18-90 V AC/DC	-	3350
8531 20 00	M2-8	8 Windows,	85-270V AC/DC 18-90 V AC/DC	-	4070
8531 20 00	M2-12	12 Windows	85-270V AC/DC 18-90 V AC/DC	12V DC	8400
8531 20 00	M2-16	16 Windows	85-270V AC/DC 24-48 VAC/DC	12V DC	11190
8531 20 00	M2-16a	16 Windows	85-270V AC/DC 24-48 VAC/DC	12V DC	11190
8531 20 00	M2-20	20 Windows	85-270V AC/DC 24-48 VAC/DC	-	12600
8531 20 00	M2-24	24 Windows	85-270V AC/DC 24-48 VAC/DC	12V DC	14050

Special Features for M2-12,M2-16,M2-16a,M2-20,M2-24

1)) Dual Source

Aux. Voltage	Standby Voltage
85-270 V AC/DC	24-48 V AC/DC
24-48 V AC/DC	85-270 V AC/DC
85-270 V AC/DC	85-270 V AC/DC

2) RS-485 Modbus

3) AC Fail/DC Fail

Note: Rs. 500 will be applied extra for each special feature.

<b>Alarm Indicators- M2 Series</b>			
	Alarm Indicator, Input voltage 24V DC		
8531 20 00	AI-4	4 Windows	1470
8531 20 00	AI-8	8 Windows	2000

HSN Code	Model	Product Description	Aux. Voltage	Stdby Voltage	Unit price (Rs.)
<b>Annunciators - M3 Series</b>					
8531 20 00	M3-4	4 Windows, 1D	85-270V AC/DC 24-48 VAC/DC	12V DC	2740
8531 20 00	M3-6	6 Windows, 1D	85-270V AC/DC 24-48 VAC/DC	12V DC	3600
8531 20 00	M3-8	8 Windows, 1D	85-270V AC/DC 24-48 VAC/DC	12V DC	4190
8531 20 00	M3-8	8 Windows, 2D	85-270V AC/DC 24-48 VAC/DC	12V DC	4170
8531 20 00	M3-12	12 Windows, 2D	85-270V AC/DC 24-48 VAC/DC	12V DC	8570
8531 20 00	M3-12	12 Windows, 3D	85-270V AC/DC 24-48 VAC/DC	12V DC	8540
8531 20 00	M3-16	16 Windows, 2D	85-270V AC/DC 24-48 VAC/DC	12V DC	11470
8531 20 00	M3-20	20 Windows, 3D	85-270V AC/DC 24-48 VAC/DC	12V DC	12830
8531 20 00	M3-24	24 Windows, 3D	85-270V AC/DC 24-48 VAC/DC	12V DC	14020
8531 20 00	M3-32	32 Windows, 4D	85-270V AC/DC 24-48 VAC/DC	12V DC	18150
8531 20 00	M3-40	40 Windows, 5D	85-270V AC/DC 24-48 VAC/DC	12V DC	22100

#### Special Features

1) Dual Source

2) RS-485 Modbus

3) AC Fail/DC Fail

4) Repeat Relay

Aux. Voltage	Standby Voltage
85-270 V AC/DC	24-48 V AC/DC
24-48 V AC/DC	85-270 V AC/DC
85-270 V AC/DC	85-270 V AC/DC

Note: Rs. 500 will be applied extra for each special feature.



HSN Code	Model	Product Description	Voltage	Time Range	Unit price (Rs.)
<b>Buzzer</b>					
8531 10 90	ESB-03	Electronic Solid State Buzzer	Aux.85-270V AC/DC , 24V AC/DC		860
<b>Production Preset Counter</b>					
General description Preset Production Counter, Rly 1C/O					
9029 10 90	CT5	5Digits with thumb wheel setting	85-270 V AC/DC	1-99,999	3140
9029 10 90	H3CT-5U	5 Digits with count sensitivity programmable	85-270 V AC/DC	1-99,999	2080
<b>Digital timer</b>					
General description Prg Dig(Up) Multifunctional timer - On delay / Interval / Cyclic					
9106 90 00	H3PT-MU	Rly1C/O instt, 1C/O Dly or 2C/O Dly, 48x48	85-270 V AC/DC	0.1S-99H59M	1330
9106 90 00	C3PT-MU	Rly 1C/O Instt, 1C/O Dly or 2C/O Dly, 72x72	85-270 V AC/DC	0.1S-99 H59M	1950
9106 90 00	E3PT-MU	Rly1C/O Instt, 2C/Odly or 3C/O Dly, 96x96	85-270 V AC/DC	0.1S-99H59M	2060
<b>Temperature Controllers</b>				<b>Temp. Range</b>	
General description - 1set point, 1display 1Rly c/o, J/K/PT-100					
9027 80 00	H3TX-Ua	Dimension: 48x48	85-270 V AC/DC	Jtype - 00-600°C Ktype - 00-1200°C	1560
9027 80 00	TX7-Ua	Dimension: 72x72	85-270 V AC/DC	PT-100 - -1000-400°C (On/Off)*	1650
9027 80 00	EX9-Ua	Dimension: 96x96	85-270 V AC/DC	PT-100 - -00-400°C (self tune)*	1720
General description - 1set point, 1display 1Rly c/o + 1SSR, J/K/PT-100					
9027 80 00	H3TX-U-RS	Dimension: 48x48	85-270 V AC/DC	Jtype - 0 <sup>0</sup> -600°C Ktype - 0 <sup>0</sup> -1200°C	1660
9027 80 00	EX9-U-RS	Dimension: 96x96	85-270 V AC/DC	PT-100 - -100 <sup>0</sup> -400°C (On/Off)* PT-100 - -0 <sup>0</sup> -400°C (self tune)*	2350
General description - 1set point, 2display 1Rly c/o, J/K/PT-100					
9027 80 00	H3TX-2U	Dimension: 48x48	85-270 V AC/DC	Jtype - 0 <sup>0</sup> -600°C	2170
9027 80 00	TX7-2U	Dimension: 72x72	85-270 V AC/DC	Ktype - 0 <sup>0</sup> -1200°C	2170
9027 80 00	EX9-2U	Dimension: 96x96	85-270 V AC/DC	PT-100 - -0 <sup>0</sup> -400°C *	2450
General description - 1set point, 2display 1Rly c/o + 1SSR, J/K/PT-100					
9027 80 00	H3TX-2U-RS	Dimension: 48x48	85-270 V AC/DC	Jtype - 0 <sup>0</sup> -600°C Ktype - 0 <sup>0</sup> -1200°C	1660
9027 80 00	EX9-2U-RS	Dimension: 96x96	85-270 V AC/DC	PT-100 - -0 <sup>0</sup> -400°C *	2450
General description - 2set point, 2display Heater type 1Rly c/o per set point, J/K/PT-100					
9027 80 00	H3TX-2H-U	Dimension: 48x48	85-270 V AC/DC	Jtype - 0 <sup>0</sup> -600°C	2360
9027 80 00	TX7-2H-U	Dimension: 72x72	85-270 V AC/DC	Ktype - 0 <sup>0</sup> -1200°C	2360
9027 80 00	EX9-2H-U	Dimension: 96x96	85-270 V AC/DC	PT-100 - 0 <sup>0</sup> -400°C *	2740
General description - 2set point, 2display Alarm type 1Rly c/o per set point, J/K/PT-100					
9027 80 00	H3TX-2A-U	Dimension: 48x48	85-270 V AC/DC	Jtype - 0 <sup>0</sup> -600°C	2360
9027 80 00	TX7-2A-U	Dimension: 72x72	85-270 V AC/DC	Ktype - 0 <sup>0</sup> -1200°C	2360
9027 80 00	EX9-2A-U	Dimension: 96x96	85-270 V AC/DC	PT-100 - 0 <sup>0</sup> -400°C *	2740
<b>Temperature Controllers</b>					
General description Multi function-Fwd/Rev, 2set point, 2display, 1Rly c/o per set point, J/K/PT-100					
9027 80 00	H3TX-MU	Dimension: 48x48	85-270 V AC/DC	Jtype - 0 <sup>0</sup> -600°C Ktype - 0 <sup>0</sup> -1200°C	1640
9027 80 00	EX9-MU	Dimension: 96x96	85-270 V AC/DC	PT-100 - 0 <sup>0</sup> -400°C *	2250
General description Multi function-Fwd/Rev, 2set point, 2display, 1Rly c/o per set point+1SSR, J/K/PT-100					
9027 80 00	H3TX-MU-RS	Dimension: 48x48	85-270 V AC/DC	Jtype - 0 <sup>0</sup> -600°C Ktype - 0 <sup>0</sup> -1200°C	1710
9027 80 00	EX9-MU-RS	Dimension: 96x96	85-270 V AC/DC	PT-100 - 0 <sup>0</sup> -400°C *	2350

**Note:** \*PT-100 in case of T and E series max temp limit is 300°C

HSN Code	Model	Product Description	Voltage	Range	Class	Unit price (Rs.)
<b>Energymeters</b>						
<b>General description AC Multi function meters 3p4w, RS 485</b>						
9030 39 10	EMS-01	Multifunction Meter with RS485	85-270 V AC/DC	3Phase 4Wire	1	6390
9030 39 10	EMS-01x	Multifunction Meter with WiFi, w/o RS485	240 VAC/DC	3Phase 4Wire	1	6470
9030 39 10	EMS-01T	Multifunction Meter with THD and RS485	85-270 V AC/DC	3Phase 4Wire	1	6820
9030 39 10	EMS-03	KWh Meter	85-270 V AC/DC	3Phase 4Wire	1	4420
9030 39 10	EMS-09	Basic/Energy Meter	85-270 V AC/DC	3Phase 4Wire	1	4780
9030 39 10	EMS-09m	Basic Energy Meter with counter	85-270 V AC/DC	3Phase 4Wire	1	4890
9030 39 10	EMS-17	Dual Source Energy Meter	85-270 V AC/DC	3Phase 4Wire	1	6060
9030 39 10	EMS-15	Maximum Demand Indicator	85-270 V AC/DC	3Phase 4Wire	1	7360
9030 39 10	EMS-15C	Maximum Demand Controller	85-270 V AC/DC	3Phase 4Wire	1	9100
<b>General description DC Multi function meters RS 485</b>						
9030 39 10	SNM-03 V6.0	Input 5V-1000VDC	85V-270VAC/DC		-	5280
9030 39 10	DCM-01	Bidirectional Solar Energymeter RS485	85-270 V AC/DC			5620
<b>Basic Panel meters</b>						
<b>General description Size g6xg6</b>						
9030 39 10	EMS-11	Ammeter	110 V AC	3Phase 4Wire	1	1260
9030 39 10	EMS-11	Ammeter	240 V AC	3Phase 4Wire	1	1260
9030 39 10	EMS-12	Volt Meter	110 V AC	3Phase 4Wire	1	1120
9030 39 10	EMS-12	Volt Meter	240 V AC	3Phase 4Wire	1	1130
<b>Basic Panel meters</b>						
<b>General description Size g6xg6</b>						
9030 39 10	EMS-11s	Single Phase Ammeter	240 V AC		1	1050
9030 39 10	EMS-12s	Single Phase Volt Meter	240 V AC		1	1050
9030 39 10	EMS-13	Frequency Meter	110 V AC	3Phase 4Wire		1210
9030 39 10	EMS-13	Frequency Meter	240 V AC	3Phase 4Wire		1270
9030 39 10	EMS-18 V6.0	VAF Meter Aux.'Y'Vtg I/P3P4W	85-270V AC/DC	3Phase 4Wire	-	1850
9030 39 10	DPM-01	Voltage Current Meter	240 V AC	Single Phase	1	1000
<b>General description Size g6x48</b>						
9030 39 10	EMS-11a	Ammeter	240 V AC	3Phase 4Wire	1	1070
9030 39 10	EMS-12a	Volt Meter	240 V AC	3Phase 4Wire	1	880
9030 39 10	EMS-13a	Frequency Meter	240 V AC	3Phase 4Wire		880
<b>RS 485 - RS 232 Converter</b>						
9030 39 10	EA232/EA485	RS232/RS485 Converter	85-270 V AC/DC			3650

**Note:** Rs. 500 extra for 0.5 class in case of Energymeters & Basic Panel Meters.

Rs.1000 for 0.2 class in case of Energymeters & Basic Panel Meters.

HSN Code	Model	Product Description	Voltage	Time Range	Unit price (Rs.)
<b>Single Phase Preventor</b>					
<b>General Description Phase Monitoring Device SelfPwrđ,3P3W, DinRail Mount TDT Factoryset</b>					
8536 90 90	PMD-01	Rly1C/O Phase fail, reverse, unbalance , UV 2.0	Self powered	440 V AC	1260
8536 90 90	PMD-01a	Rly2C/O Phase fail, reverse, unbalance , UV V2.0	Self powered	440 VAC	1240
<b>General Description Single Phase Preventer Selfpwrđ,3P3W Din Rail Mount Rly1C/O TDT Factoryset</b>					
8536 90 90	PMD-02	Phase fail, reverse, UV	Self powered	415 V AC	960
8536 90 90	PMD-03	Phase fail, reverse, UV	Self powered	415 V AC	880
8536 90 90	SPP-T	Phase fail, reverse, unbalance	Self powered	415 V AC	1150
<b>Auto Switch</b>				<b>Input Voltage</b>	
8536 90 90	SPPT	V2.0 Auto Switch Single Phase Preventer, 3P 3W Rly 1C/O		415 V AC	730
<b>Reverse Power Device</b>					
8536 90 90	RPD-01	Reverse Power Monitoring Device Dinrail mount Rly1C/O self powered	240 V AC		3530
<b>Digital Monitoring Devices</b>					
<b>Description</b>					
8536 90 90	PVMD	SelfPwrđ Panel Mount	Self powered	415 V AC	3030
8536 90 90	PVMD-G	Self Pwrđ Din Rail Mount	Self powered	415 V AC	3060
8536 90 90	PVMR-A	With Aux supply Panel Mount	85-270 V AC/DC	415 V AC	3090
<b>General Description Phase Voltage Current Monitoring Device, Input-3P 4W, Rly 1C/O,10A</b>					
8536 90 90	PVIMD	SelfPwrđ Panel Mount	Self powered	415 V AC	3610
8536 90 90	PVIMD-G	Self Pwrđ Din Rail Mount	Self powered	415 V AC	3610
8536 90 90	PVIMR-A	With Aux supply Panel Mount	100-270 V AC		3460
<b>Digital Monitoring Devices</b>					
<b>General Description Phase Voltage Current Monitoring Device, Input-3P 4W, Rly 1C/O,10A, RS 485, Panel Mount</b>					
8536 90 90	PVIMD-R	Y Vltg Aux supply	85-270 V AC/DC	415V AC	5470
8536 90 90	PVIMD -Ra	Y Vltg Aux supply	85-270 V AC/DC	415V AC	5470
<b>General Description Power Monitoring Relaywith 100mm CBCT, Input-3P 4W, Rly 1C/O,10A</b>					
8536 90 90	PMR-01A	With Aux supply Panel Mount	100-270 V AC	415 V AC	5230
<b>Digital Time switch</b>					
<b>General Description Daily Time Switch 4 Switching per day Rly 1C/O16A</b>					
9107 00 00	TS-203	Panel Mount External battery (2AA 1.5V)	240 V AC	1M-23H59M	1610
9107 00 00	TS-203R	Panel Mount Rechargeable battery	240 V AC	1M-23H59M	1610
9107 00 00	TS-203B	Din Rail Mount External battery (2AA 1.5V)	240 V AC	1M-23H59M	1610
<b>Power Supply Module</b>			<b>O/p</b>	<b>Input Voltage</b>	
<b>General Description Switch Mode Power Supply 24V DC</b>					
8504 31 00	MS-01	Output 1A	24VDC,24W	192V-264VAC	1270
8504 31 00	MS-02	Output 0.63A	24VDC,15W	170V-300VAC	2160
8504 31 00	MS-02	Output 1.04A	24VDC,25W	170V-300VAC	2150
8504 31 00	MS-02	Output1.46A,	24VDC,35W	170V-300VAC	2150
8504 31 00	MS-02	Output 2.1A	24V DC,50W	170V-300VAC	1790
8504 31 00	MS-03	Output 5A	24VDC,120W	170V-300VAC	3250
<b>General Description Switch Mode Power Supply 15V DC</b>					
8504 31 00	MS-02	Output 2.1A,	15V DC,31.5W	170V-300VAC	2150



HSN Code	Model	Product Description	Output	Input Voltage	Unit price (Rs.)
<b>Power Supply Module</b>					
<b>General Description Switch Mode Power Supply 12V DC</b>					
8504 31 00	MS-02	Output 1.25 A	12VDC,15W	170V-300VAC	2150
8504 31 00	MS-02	Output 2.08 A	12VDC,25W	170V-300VAC	2150
8504 31 00	MS-02	Output 2.9A	12VDC,35W	170V-300VAC	2150
8504 31 00	MS-02	Output 4.2A	12VDC,50W	170V-300VAC	2150
<b>General Description Switch Mode Power Supply 5V DC</b>					
8504 31 00	MS-05	Output 1A,	5VDC,5W	170V-300VAC	780
8504 31 00	MS-02	Output 3A,	5VDC,15W	170V-300VAC	2150
8504 31 00	MS-02	Output 5A,	5VDC,25W	170V-300VAC	2150
8504 31 00	MS-02	Output6A,	5VDC,30W	170V-300VAC	2150
<b>Tachometer</b>			<b>Battery Voltage</b>	<b>RPM range</b>	
9029 20 90	DT-2001B	Hand Held LCD Tachometer 6 VDC (4x1.5VAA size battery) 1-99999RPM	6V (1.5V x4cells)	1-99,999	3130
<b>Photo Sensing Relay</b>			<b>Aux Voltage</b>	<b>Time range</b>	
8448 32 00	EALS-1003	Photo Sensing & Control Relay 240VAC 2S-20S Rly1C/O OFFDly	240V AC	2S - 20s	2130
8448 32 00	EAPRE-01	Photo Sensing & Control Relay - Emitter Probe	NA	NA	1420
8448 32 00	EAPRR-01	Photo Sensing & Control Relay - Receiver Probe	NA	NA	1420
<b>Light switch</b>			<b>Aux Voltage</b>	<b>Time range</b>	
8448 32 00	EALS-4505	Electronic Stop Motion Light Switch 240VAC 0.3S-30S Rly1C/O ON/OFFDly	240V AC	0.3s - 30s	2130
8448 32 00	EALSE-01	Electronic Stop Motion Light Switch - Emitter Probe	NA	NA	1420
8448 32 00	EALSR-01	Electronic Stop Motion Light Switch - Receiver Probe	NA	NA	1420
<b>Under Voltage Relay</b>					
8536 49 00	ETR-01	Under Voltage Time Relay I/P 3Phase 4Wire ONDly	415 V AC	5m-15m	840
8536 49 00	ETR-02	Under Voltage Timer Relay ONDLY	230 V AC	5m-15m	790

Y' Vtg - 85V to 270V AC/DC

▪ For other CBCT dimensions, please contact us.

**Note:**

- \* All prices are Ex-factory with standard packing.
- \* Prices are inclusive of GST.
- \* Prices are subject to revision without notice.
- \* Larger quantities are eligible for better discount.



**DODIA ELECTRICALS**

Visit us at

[www.dodiaelectricals.com](http://www.dodiaelectricals.com)

Email id

[sales@dodiaelectricals.com](mailto:sales@dodiaelectricals.com)

Add.: 9/11, Ground Floor, Picket Cross Road,  
Lohar Chawl, Mumbai - 400002

Whats App / Contact

+91 98338 24773